

2112 INDUSTRIAL P.O. BOX 124
HOWELL, MI 48843

10N0239
FILTER RAY

www.nyatex.com

rev. date: 10/03/2016

Designed Uses:

An excellent general purpose coating for wood or metal. 10N0239 provides good adhesion, ultra-violet resistance, and excellent water resistance. The normal fast air dry can be accelerated with heat, but should not exceed 250 °F. **Settling may occur over time with this product. Mix well before each use.**

Technical Specifications:

Odor and Appearance: solvent odor, clear

Viscosity: 45-50 sec. #4 Ford Cup @25 °C
15-18 sec. #2 Zahn Cup @25 °C

Solids: 36 ± 2%

Flash Point: 41 °F.

Minimum Film Temp.: N/A

Base: Acrylic

Density: 7.8 ± 0.2 lbs/gal.

pH: N/A

Film: Clear with low-gloss

Borax Tolerance: N/A

FDA Status: N/A

APPLICATION:

Surface Preparation:

Substrate must be clean, dry, and free of contaminants; e.g., release agents, dirt, dust, old paint, etc.

Application:

10N0239 can be sprayed or dipped

Open Time:

Varies with application method and environmental conditions

Clean Up:

May be removed with aromatic solvents before completely cured.

Storage:

Store in controlled dry area. Keep well sealed and at ambient temperature.

Classified as FLAMMABLE by DOT and should be treated accordingly. Full containers should be stored away from heat, sparks, open flame and strong oxidizers. NEVER use welding/cutting torches on/near containers because vapors can ignite explosively. Static discharge could cause ignition. Empty containers containing residue (liquid or vapor) can be dangerous.

Recommended Inventory: 90 days
(1 yr shelf life)

Precautions:

Health:

Work in well ventilated areas. Avoid prolonged or repeated contact with skin. Wear safety glasses. More details can be found on accompanying MSDS.

Environmental:

Incinerate or bury in landfill in accordance with all local, state, and federal regulations.

Standard Packaging:

52 Gallon Steel Drums, 5 Gallon Steel Pails, 1 Gallon Cans