

2112 INDUSTRIAL P.O. BOX 124
HOWELL, MI 48843

NC-1331
H.D. Maintenance Cleaner

www.nyatex.com

rev. date: 03/04/14

NC-1331 is a heavy-duty liquid compound formulated for the special needs of industry. It comes in highly concentrated form and is compounded so that its alkalinity is maintained even when diluted.

Designed Uses:

NC-1331 was developed for use on oily shop floors. This cleaner can be used in the routine maintenance of tile. Machine tools and equipment are easily cleaned with NC-1331. This general cleaner can be used on any surface not harmed by soap and water.

Physical Characteristics:

NC-1331 is an excellent, non-flammable, water-soluble, degreaser with properties to remove heavy soil and grease build-up. It comes in highly concentrated form. It can be diluted to a concentration that will suit the soiled condition and the cleaning procedure used. NC-1331 is non-corrosive on ferrous metals so it can be used on machine tools and equipment. This industrial cleaner is free of phosphates and contains biodegradable surfactants.

Technical Specifications:

Odor and Appearance: Mild smelling, thin blue liquid

FDA Status: N/A

Density: 8.6 +/- 0.2 lbs/gal.

Miscibility. : Complete in water

Solids: NA

pH: 12.5 +/- 0.5

Flash Points: >200 °F

Film: N/A

Minimum Film Temp. : N/A

Borax Tolerance: N/A

Application:

It is recommended that NC-1331 be used in solution with water in accordance with the chart below. The user should experiment and adjust the ratio of the solution to the soil condition and the cleaning procedure. NC-1331 can be used in all methods of application whether they be the traditional mop and bucket, automatic floor scrubbers or high intensity sprayers. All surfaces that have been cleaned should be rinsed thoroughly with water.

-Glass and painted surfaces...1-2 fl.oz. / gal. Water

-Shop floors-machine scrub...4-6 fl.oz. / gal. Water

-Shop floors-hand mopping...6-12 fl.oz. / gal. Water

-Tile floors ...6-12 fl.oz. / gal. Water

-Tile floors-wax removal ...32-48 fl.oz. / gal. Water

-Machine tools & equipment...8-16 fl.oz. / gal. Water

Precautions:

Rubber gloves are recommended, as the product should not come into repeated or prolonged contact with skin. If the cleaning solution is being applied with pressure equipment, goggles must be worn to prevent irritation of the eyes. More details can be found on the Material Safety Data Sheet.

DOT Label:

Not regulated, Compound Cleaning Liquid

Standard Packaging:

275 Gallon Totes

55 Gallon Steel Drums

5 Gallon Steel Pails